

	# OF VEHICLES	BED WIDTH (IN.)	BED LENGTH (IN.)	OVERALL LENGTH (IN.)	RAMP STANDARD	TILT BED	CARRYING CAPACITY W/O BRAKES (LB.)	GVWR W/O BRAKES (LB.)	CARRYING CAPACITY WITH BRAKES (LB.)	GVWR WITH BRAKES (LB.)	TRAILER WEIGHT (LB.)	NO. OF AXLES	HITCH HEIGHT (IN.)	DECK HEIGHT (IN.)	STANDARD TIRES	TIRE UPGRADE OPTIONS*	TONGUE STYLE	PLYWOOD THICKNESS (IN.)	TONGUE JACK	TIE DOWNS	BRAKE OPTIONS
ELITE 22-101	4	101	264	333	YES	NO	1520	2995	3525	5000	1475	2	24	29	ST145/R12E	D E F G	SP	5/8"	YES	QUICKSLIDE	1 OR 2 AXLES
ELITE 16-101	3	101	192	261	YES	NO	1995	2995	4000	5000	1000	2	24	29	ST145/R12E	D E F G	SP	5/8"	YES	QUICKSLIDE	1 OR 2 AXLES
ELITE 12VR-101	2	101	144	223	YES	NO	1615	2200	N/A	N/A	585	1	20	26	20.5X10C	C D E	SP	5/8"	NO	QUICKSLIDE	N/A
XT12VR-101 QP	2	101	144	215	YES	NO	1655	2200	N/A	N/A	545	1	18	24	20.5X10C	C D E	SP	1/2"	NO	QUICKSLIDE	N/A
XT12VR-101 F	2	101	144	220	YES	NO	1955	2500	N/A	N/A	545	1	24	33	ST205/75D	-	SP	1/2"	NO	SINGLE	N/A
XT10-101 QP	2	101	120	172	NO	YES	1505	1880	N/A	N/A	375	1	18	24	18.5X8C	B C D	WB	1/2"	NO	QUICKSLIDE	N/A
XT12-101 SQ	2	101	144	196	NO	YES	1735	2200	N/A	N/A	465	1	18	24	20.5X10C	C D E	WB	1/2"	NO	PRTL QUICKSLIDE	N/A
XT11-101 SQ	2	101	132	184	NO	YES	1455	1880	N/A	N/A	425	1	18	24	18.5X8C	B C D	WB	1/2"	NO	PRTL QUICKSLIDE	N/A
XT10-101 SQ	2	101	120	172	NO	YES	1505	1880	N/A	N/A	375	1	18	24	18.5X8C	B C D	WB	1/2"	NO	PRTL QUICKSLIDE	N/A
XT10-101	2	101	120	172	NO	YES	1505	1880	N/A	N/A	375	1	18	24	18.5X8C	B C D	WB	1/2"	NO	SINGLE	N/A
ELITE5	1	62	144	196	NO	YES	1825	2200	N/A	N/A	375	1	17	22	20.5X10C	C D E	SP	5/8"	NO	QUICKSLIDE	N/A
XT4.5	1	53	120	172	NO	YES	1350	1700	N/A	N/A	350	1	17	21	18.5X8C	A	SP	1/2"	NO	SINGLE	N/A

Recommended tongue weight 7-10% of GVWR. It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate state motor vehicle department.

*TIRE UPGRADE OPTIONS

OPTION	TIRE	RIM
A	5.30X12 C	painting silver
B	20.5X10 C	painting silver
C	20.5X10 E	painting silver

OPTION	TIRE	RIM
D	ST145/R 12E	painting silver or aluminum
E	ST175/80 D13C	painting silver or aluminum
F	ST205/75 D14C	painting silver

OPTION	TIRE	RIM
G	ST205/75 R14C	aluminum

Note: Some tire upgrades require spacer kits. See your dealer.