

	TC118	TC128	TC118-LR	TC128-LR	TC167
# OF VEHICLES	2	2	2	2	2
USABLE DECK WIDTH (IN.)	98	98	98	98	80.5
USABLE DECK LENGTH (IN.)	127	143	127	143	191
OVERALL WIDTH (IN.)	101.5	101.5	101.5	101.5	101.5
OVERALL LENGTH (IN.)	186	202	186	202	254
OVERALL HEIGHT (IN.)	91	91	87	87	90
DOOR OPENING (IN.) width x height	93 x 63	93 x 63	93 x 63	93 x 63	76 x 63
CARRYING CAPACITY W/O BRAKES (LB.)	2025	2000	2025	2000	1815
GVWR W/O BRAKES (LB.)	2995	2995	2995	2995	2995
CARRYING CAPACITY WITH BRAKES (LB.)	2030	2005	2030	2005	2320
GVWR WITH BRAKES (LB.)	3000	3000	3000	3000	3500
TRAILER WEIGHT (LB.)	970	995	970	995	1180
NUMBER OF AXLES	1	1	1	1	1
STANDARD TIRES	20.5x10E	20.5x10E	ST145/R12E	ST145/R12E	ST205/75D14C
TIRE AND WHEEL UPGRADE OPTIONS	ST145/R12E painted silver or aluminum	ST145/R12E painted silver or aluminum	ST145/R12E aluminum	ST145/R12E painted silver or aluminum	ST205/75R14C aluminum
HITCH HEIGHT (IN.)	19	19	15	15	18
QUICKSLIDE CHANNELS	2 partial deck length	2 partial deck length	2 partial deck length	2 partial deck length	2 full deck length
FLUSH MOUNTED D-RING TIE DOWNS	2	2	2	2	N/A

Measure your particular vehicles for needed model size. Recommended tongue weight for all enclosed trailers is 7-10% of GVWR. Please note: It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Department. Contact your local dealer for order lead times. All trailers ordered without brakes will have a GVWR of 2995#. Specifications, parts, and accessories can change without notice.