

	BED WIDTH (IN.)	BED LENGTH (FT.)	BED LENGTH WITH 5' V-NOSE (FT.)	OVERALL LENGTH (FT.)	CARRYING CAPACITY (LB.)	GVWR (LB.)	TRAILER WEIGHT (LB.)	NO. OF AXLES	BALL SIZE (LB.)	HITCH HEIGHT (IN.)	STANDARD TIE DOWN	STANDARD TIRES (ALUMINUM OR TML RIMS)
XT-147	80.5	14	19	22.5	3550	5000	1450	2	2	18	4 - 1000 LB. D-RING	ST205/75 R14C
XT-187	80.5	18	23	26.5	4350	6000	1650	2	2	18	6 - 1000 LB. D-RING	ST205/75 R14C
XT-227	80.5	22	27	30.5	3900	6000	2100	2	2	18	6 - 1000 LB. D-RING	ST205/75 R14C
XT-247	80.5	24	29	32.5	3675	6000	2325	2	2	18	6 - 1000 LB. D-RING	ST205/75 R14C
XT-168	98	16	21	24	3300	5000	1700	2	2	25	6 - 1000 LB. D-RING	175/80 R13D
XT-208	98	20	25	28	3850	6000	2150	2	2	25	6 - 1000 LB. D-RING	175/80 R13D
XT-228	98	22	27	30	3725	6000	2275	2	2	25	6 - 1000 LB. D-RING	175/80 R13D
XT-248	98	24	29	32	3600	6000	2400	2	2	25	6 - 1000 LB. D-RING	175/80 R13D

	Front Door Opening 6' Box (W" X H")	Rear Door Opening 6' Box (W" X H")	Front Door Opening 6'6" Box (W" X H")	Rear Door Opening 6'6" Box (W" X H")
XT 7' Wide	62 x 67	76 x 70	62 x 73	76 x 76
XT 8' Wide	62 x 67	92 x 70	62 x 73	92 x 76

Measure your particular vehicles for needed model size. Recommended tongue weight for all enclosed trailers is 7-10% of GVWR. Please note: It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Department. Contact your local dealer for order lead times. All trailers ordered without brakes will have a GVWR of 2995 lbs. Specifications, parts, and accessories can change without notice. Trailers may be shown with options not standard.