

MODEL	# OF UNITS	TIRE/RIM & AXLE CHOICE		GVWR	CARRYING CAPACITY	TRAILER WEIGHT	OVERALL WIDTH	OVERALL LENGTH	HITCH HEIGHT	COUPLER SIZE	AXLE TYPE	BRAKES
ELITE WCII	2	#07355 20.5X10E #03392 ST175/80D13C #08875 ST145/R12E	#09942 ST175/80D13C ALUM. #10384 ST145/R12E ALUM.	2700	2335	365	101.5	189	19	2	TORSION	N/A
ELITE WCIV-SBD	4	#03392 ST175/80D13C #08875 ST145/R12E	#09942 ST175/80D13C ALUM. #10384 ST145/R12E ALUM.	5400	4200	1200	102	343.5	21	2	TORSION	10" Surge Disc on 1 axle. Surge Disc option available on 2nd axle.

Overall lengths are based on the bunks setup in the farthest position to the rear of the trailer. Hitch height is based on standard tires, upgraded tires will change loaded hitch heights. Prices and specifications may change without notice. Please note: It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Department. Brake options will change the overall length of trailer. Recommended tongue weight 7-10% of GVWR. Five year limited warranty when registered online within 45 days of purchase at tritontrailers.com. Non-registered trailers have one year warranty.