

	BED WIDTH (IN.)	BED LENGTH (IN.)	OVERALL WIDTH (IN.)	OVERALL LENGTH (IN.)	RAMP STANDARD	TILT BED	CARRYING CAPACITY W/O BRAKES (LB.)	GVWR W/O BRAKES (LB.)	CARRYING CAPACITY WITH BRAKES (LB.)	GVWR WITH BRAKES (LB.)	TRAILER WEIGHT (LB.)	NO. OF AXLES	HITCH HEIGHT	DECK HEIGHT	PLYWOOD THICKNESS (IN.)	STANDARD TIRES*	TIRE UPGRADE OPTIONS*	TONGUE JACK	LOADING STYLE	COUPLER (IN.)	BRAKE OPTIONS**
ATV88	79	104	79.75	150	YES	NO	1520	1880	N/A	N/A	360	1	19	22	1/2	A	B, C, E, F	NO	SIDE/REAR	2	N/A
ATV128	79	152	79.75	202	YES	NO	2475	2995	N/A	N/A	520	1	22	25.5	1/2	E	F, K, L	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV128	79	152	79.75	202	YES	NO	N/A	N/A	2980	3500	520	1	22	25.5	1/2	N/A	M, O	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV128-2	79	152	79.75	202	YES	NO	2315	2995	3720	4400	680	2	22	25.5	1/2	B	C, E, F	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV168	79	200	79.75	250	YES	NO	2215	2995	3620	4400	780	2	22	25.5	1/2	B	C, E, F	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV88-TR	79	104	79.75	150	YES	NO	1470	1880	N/A	N/A	410	1	19	22	1/2	A	B, C, E, F	NO	SIDE/REAR	2	N/A
ATV128-TR	79	152	79.75	202	YES	NO	2425	2995	N/A	N/A	570	1	22	25.5	1/2	E	F, K, L	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV128-TR	79	152	79.75	202	YES	NO	N/A	N/A	2930	3500	570	1	22	25.5	1/2	N/A	M, O	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV128-2-TR	79	152	79.75	202	YES	NO	2265	2995	3670	4400	730	2	22	25.5	1/2	B	C, E, F	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV168-TR	79	200	79.75	250	YES	NO	2165	2995	3570	4400	830	2	22	25.5	1/2	B	C, E, F	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV1490-TR	90	168	90.5	219	YES	NO	2281	2995	2586	3200	714	1	23	27	5/8	E	F, K, L	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV1490-2-TR	90	168	90.5	219	YES	NO	2154	2995	4159	5000	841	2	23	27	5/8	E	F, G, H, K, L	YES	SIDE/REAR	2	SURGE/ELECTRIC
ATV1890-TR	90	216	90.5	267	YES	NO	2001	2995	4006	5000	994	2	23.5	27.5	5/8	E	F, G, H, K, L	YES	SIDE/REAR	2	SURGE/ELECTRIC

### \*TIRE OPTIONS

OPTION	TIRE	PART NUMBER	OPTION	TIRE	PART NUMBER	OPTION	TIRE	PART NUMBER	OPTION	TIRE	PART NUMBER	OPTION	TIRE	PART NUMBER
A	18.5 X 8C SILVER	02435	B	20.5 X 10 C SILVER	03165	C	20.5 X 10 E SILVER	07355	E	ST145/R12E SILVER	08875	F	ST145/R12E ALUMINUM	10384
G	ST175/80D13C SILVER	03392	K	ST175/80R-13D WHITE	07107	L	175/80R13D ALUMINUM T08	09475	M	ST205/75D14 SILVER	06672	O	ST205/75R14 ALUMINUM T08	06193

Make sure that the trailer has the carrying capacity and deck space for your specific loads. Recommended tongue weight 7-10% of GVWR. Upgraded tires will change deck heights. Some tire upgrades require spacer kits. See your dealer. It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Dept. Contact your authorized Triton Trailers, LLC dealer for specifications, pricing and lead times. Due to continuous product improvements; standard features, optional accessories and specifications are subject to change without notice or obligation. Triton Trailers, LLC reserves the right to make changes to models or discontinue models without notice or obligation.

\*\*Brake options will change the overall length of trailer. Second axle brakes can be added when one is standard.