

	BED WIDTH (IN.)	BED LENGTH (IN.)	OVERALL WIDTH (IN.)	OVERALL LENGTH (IN.)	RAMP STANDARD	TILT BED	CARRYING CAPACITY W/O BRAKES (LB.)	GVWR W/O BRAKES (LB.)	CARRYING CAPACITY WITH BRAKES (LB.)	GVWR WITH BRAKES (LB.)	TRAILER WEIGHT (LB.)	NO. OF AXLES	HITCH HEIGHT	DECK HEIGHT	PLYWOOD THICKNESS (IN.)	STANDARD TIRES	TIRE UPGRADE OPTIONS	TONGUE JACK	LOADING STYLE	COUPLER (IN.)	BRAKE OPTIONS*
TILT1072	72	120	93	177	NO	YES	2495	2995	3000	3500	500	1	15.5	18.5	ALUM.	M	N, O	YES	REAR	2	ELECTRIC
TILT1282	80.75	144	102	192	NO	YES	2295	2995	2800	3500	700	1	14.5	18.5	ALUM.	M	N, O	YES	REAR	2	ELECTRIC
TILT1482	80.75	168	102	216	NO	YES	2168	2995	2673	3500	827	1	14.5	18.5	ALUM.	M	N, O	YES	REAR	2	ELECTRIC

**\*TIRE OPTIONS**

OPTION	TIRE	PART NUMBER	OPTION	TIRE	PART NUMBER	OPTION	TIRE	PART NUMBER
M	ST205/75D14 SILVER	06672	N	ST205/75R14C SILVER	14113	O	ST205/75R14 ALUMINUM T08	06193

Make sure that the trailer has the carrying capacity and deck space for your specific loads. Recommended tongue weight 7-10% of GVWR. Upgraded tires will change deck heights. Some tire upgrades require spacer kits. See your dealer. It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Dept.

Contact your authorized Triton Trailers, LLC dealer for specifications, pricing and lead times. Due to continuous product improvements; standard features, optional accessories and specifications are subject to change without notice or obligation. Triton Trailers, LLC reserves the right to make changes to models or discontinue models without notice or obligation.

\*Brake options will change the overall length of trailer. Second axle brakes can be added when one is standard.