

	BED WIDTH (IN.)	BED LENGTH (IN.)	OVERALL WIDTH (IN.)	OVERALL LENGTH (IN.)	RAMP STANDARD	TILT BED	CARRYING CAPACITY W/O BRAKES (LB.)	GVWR W/O BRAKES (LB.)	CARRYING CAPACITY WITH BRAKES (LB.)	GVWR WITH BRAKES (LB.)	TRAILER WEIGHT (LB.)	NO. OF AXLES	HITCH HEIGHT	DECK HEIGHT	PLYWOOD THICKNESS (IN.)	STANDARD TIRES	TIRE UPGRADE OPTIONS	TONGUE JACK	LOADING STYLE	COUPLER (IN.)	BRAKE OPTIONS*
UT12	81	144	101	191	NO	NO	2215	2995	2720	3500	780	1	17	21	5/8	ST205/75D14	ST205/75R14 ALUM.	YES	REAR	2	SURGE/ELECTRIC
UT12-2	81	144	101	192	NO	NO	2095	2995	5100	6000	900	2	17	21	5/8	ST205/75D14	ST205/75R14 ALUM.	YES	REAR	2	SURGE/ELECTRIC
UT16	81	192	101	238	NO	NO	1995	2995	5000	6000	1000	2	17	21	5/8	ST205/75D14	ST205/75R14 ALUM.	YES	REAR	2	SURGE/ELECTRIC
UT16-7	81	192	101	238	NO	NO	N/A	N/A	5825	7000	1175	2	17	22	1	ST205/75D14	ST205/75R14 ALUM.	YES	REAR	2 5/16	STD. 1-ELEC

Make sure that the trailer has the carrying capacity and deck space for your specific loads. Recommended tongue weight 7-10% of GVWR. Upgraded tires will change deck heights. Some tire upgrades require spacer kits. See your dealer. It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Dept. Contact your authorized Triton Trailers, LLC dealer for specifications, pricing and lead times. Due to continuous product improvements; standard features, optional accessories and specifications are subject to change without notice or obligation. Triton Trailers, LLC reserves the right to make changes to models or discontinue models without notice or obligation.

*Brake options will change the overall length of trailer. Second axle brakes can be added when one is standard.